



ULA S WHITE LIGHT

UlaS AULSI IEC AG CLR / FL112/Nx G4 04W 820 1000


Luminaire segment




COLORS



PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



SPECTRUM

2000K
CRI 80+
3-Step MacAdam

COVER

Clear

LUMINOUS FLUX*

Per segment: 431 lm
Light source (per segment): 490 lm
Per meter/feet: 431 lm/m | 131 lm/ft

EFFICACY

Luminaire: 90 lm/W
Light source: 102 lm/W

LIFETIME

L90B10 60.000h

HOUSING

Aluminum, plastic

ELECTRICAL

Segment power: 4.8 W
Power per meter/feet: 4.8 W/m
Voltage: 24 VDC

OTHER DETAILS

IP40 ingress protection
Dimmable

DIMENSIONS

Width: 16 mm (0.63")
Height: 11 mm (0.43")
Length: 1003 mm | 3.3'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.