



# ULA S WHITE LIGHT


UlaS AULSI IEC PB CLR / FL112/Nx G4 04W 822 1000  
Luminaire segment




## COLORS

 Black housing

## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



<b>SPECTRUM</b>	2200K CRI 80+ 3-Step MacAdam
<b>COVER</b>	Clear
<b>LUMINOUS FLUX*</b>	Per segment: 467 lm Light source (per segment): 531 lm Per meter/feet: 467 lm/m   142 lm/ft
<b>EFFICACY</b>	Luminaire: 97 lm/W Light source: 111 lm/W
<b>LIFETIME</b>	L90B10 60.000h
<b>HOUSING</b>	Aluminum, plastic
<b>ELECTRICAL</b>	Segment power: 4.8 W Power per meter/feet: 4.8 W/m Voltage: 24 VDC
<b>OTHER DETAILS</b>	IP40 ingress protection Dimmable
<b>DIMENSIONS</b>	Width: 16 mm (0.63") Height: 11 mm (0.43") Length: 1003 mm   3.3'

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.