



ULA M WHITE LIGHT

UlaM AULMI IEC AG EOP / FL112/Nx G4 04W 820 1000

Luminaire segment




COLORS




Grey housing

PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



16 mm
(0.63 in)

SPECTRUM
2000K
CRI 80+
3-Step MacAdam

COVER
Opal

LUMINOUS FLUX*
Per segment: 235 lm
Light source (per segment): 490 lm
Per meter/feet: 235 lm/m | 72 lm/ft

EFFICACY
Luminaire: 49 lm/W
Light source: 102 lm/W

LIFETIME
L90B10 60.000h

HOUSING
Aluminum, plastic

ELECTRICAL
Segment power: 4.8 W
Power per meter/feet: 4.8 W/m
Voltage: 24 VDC

OTHER DETAILS
IP40 ingress protection
Dimmable

DIMENSIONS
Width: 16 mm (0.63")
Height: 21 mm (0.82")
Length: 1003 mm | 3.3'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.