




ULA M WHITE LIGHT

UlaM AULMI IEC PW EOP / FL112/Nx G4 04W 822 1000


Luminaire segment




COLORS



PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



16 mm
(0.63 in)

SPECTRUM	2200K CRI 80+ 3-Step MacAdam
COVER	Opal
LUMINOUS FLUX*	Per segment: 255 lm Light source (per segment): 531 lm Per meter/feet: 255 lm/m 78 lm/ft
EFFICACY	Luminaire: 53.1 lm/W Light source: 111 lm/W
LIFETIME	L90B10 60.000h
HOUSING	Aluminum, plastic
ELECTRICAL	Segment power: 4.8 W Power per meter/feet: 4.8 W/m Voltage: 24 VDC
OTHER DETAILS	IP40 ingress protection Dimmable
DIMENSIONS	Width: 16 mm (0.63") Height: 21 mm (0.82") Length: 1003 mm 3.3'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.