

ULA M IP67 RGB COLORFUL LIGHT

UlaM.IP67 AULMO IEC AG EOP / RGB-48/Nx G5 011W L1000


Start segment




COLORS

 Grey housing

PHOTOMETRICS




SEGMENT LAYOUT



Start type segment

TECHNICAL DRAWING



SPECTRUM	3-Step MacAdam
COVER	Opal
LUMINOUS FLUX*	<p>Luminaire: 216 lm</p> <p>Light source: 480 lm</p> <p>Per meter/feet:</p> <p>Red: 47 Lm/m 14 Lm/ft</p> <p>Green: 138 Lm/m 42 Lm/ft</p> <p>Blue: 31 Lm/m 9 Lm/ft</p>
EFFICACY	<p>Luminaire: 19 lm/W</p> <p>Light source: 42 lm/W</p>
LIFETIME	L90B10 60.000h
HOUSING	Aluminum, polyurethane
ELECTRICAL	<p>Power per meter/feet: 11.52 W/m</p> <p>Voltage: 24 VDC</p>
TEMPERATURE	<p>Tc max <75°C (167°F)</p> <p>Operating: -25°C...+50°C (-13°F...122°F)</p>
OTHER DETAILS	<p>IP67 protection</p> <p>Dimmable</p> <p>Install in well-ventilated areas only</p>
DIMENSIONS	<p>Width: 16 mm (0.63")</p> <p>Height: 26 mm (1.02")</p> <p>Length: 1001.5 mm 3.3'</p>

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.