

ULA S IP67 RGB COLORFUL LIGHT

UlaS.IP67 AULSO IEC AG ECL / RGB48/Nx G5 011W L1000


Luminaire segment




COLORS

 Grey housing

PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



SPECTRUM

3-Step MacAdam

COVER

Clear

LUMINOUS FLUX*

Luminaire: 306 lm
Light source: 480 lm

Per meter/feet:

Red: 66 Lm/m | 20 Lm/ft
Green: 195 Lm/m | 60 Lm/ft
Blue: 44 Lm/m | 13 Lm/ft

EFFICACY

Luminaire: 27 lm/W
Light source: 42 lm/W

LIFETIME

L90B10 60.000h

HOUSING

Aluminum, polyurethane

ELECTRICAL

Power per meter/feet: 11.52 W/m
Voltage: 24 VDC

TEMPERATURE

Tc max <75°C (167°F)
Operating: -25°C...+50°C (-13°F...122°F)

OTHER DETAILS

IP67 protection
Dimmable
Install in well-ventilated areas only

DIMENSIONS

Width: 16 mm (0.63")
Height: 16 mm (0.63")
Length: 1003 mm | 3.3'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.