

ULA S IP67 RGB COLORFUL LIGHT

UlaS.IP67 AULSO IEC PW ECL / RGB48/Nx G5 011W L1000


Luminaire segment




COLORS

 White housing

PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



SPECTRUM	3-Step MacAdam
COVER	Clear
LUMINOUS FLUX*	Luminaire: 306 lm Light source: 480 lm Per meter/feet: Red: 66 Lm/m 20 Lm/ft Green: 195 Lm/m 60 Lm/ft Blue: 44 Lm/m 13 Lm/ft
EFFICACY	Luminaire: 27 lm/W Light source: 42 lm/W
LIFETIME	L90B10 60.000h
HOUSING	Aluminum, polyurethane
ELECTRICAL	Power per meter/feet: 11.52 W/m Voltage: 24 VDC
TEMPERATURE	Tc max <75°C (167°F) Operating: -25°C...+50°C (-13°F...122°F)
OTHER DETAILS	IP67 protection Dimmable Install in well-ventilated areas only
DIMENSIONS	Width: 16 mm (0.63") Height: 16 mm (0.63") Length: 1003 mm 3.3'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.