

# ULA S IP67 RGB COLORFUL LIGHT

UlaS.IP67 AULSO IEC AG ECL / RGB48/Nx G5 07W L1000


Luminaire segment



## COLORS

 Grey housing

## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



<b>SPECTRUM</b>	3-Step MacAdam
<b>COVER</b>	Clear
<b>LUMINOUS FLUX*</b>	<p>Luminaire: 201 lm Light source: 316 lm</p> <p><b>Per meter/feet:</b>            Red: 41 Lm/m   13 Lm/ft            Green: 132 Lm/m   40 Lm/ft            Blue: 27 Lm/m   8 Lm/ft</p>
<b>EFFICACY</b>	<p>Luminaire: 28 lm/W Light source: 44 lm/W</p>
<b>LIFETIME</b>	L90B10 60.000h
<b>HOUSING</b>	Aluminum, polyurethane
<b>ELECTRICAL</b>	<p>Power per meter/feet: 7.2 W/m Voltage: 24 VDC</p>
<b>TEMPERATURE</b>	<p>Tc max &lt;75°C ( 167°F ) Operating: -25°C...+50°C ( -13°F...122°F )</p>
<b>OTHER DETAILS</b>	<p>IP67 protection Dimmable Install in well-ventilated areas only</p>
<b>DIMENSIONS</b>	<p>Width: 16 mm (0.63") Height: 16 mm (0.63") Length: 1003 mm   3.3'</p>

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.