

ULA S IP67 RGB COLORFUL LIGHT

UlaS.IP67 AULSO IEC PB ECL / RGB48/Nx G5 07W L1000


Luminaire segment




COLORS

 Black housing

PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



SPECTRUM 3-Step MacAdam

COVER Clear

LUMINOUS FLUX* Luminaire: 201 lm
Light source: 316 lm

Per meter/feet:
Red: 41 Lm/m | 13 Lm/ft
Green: 132 Lm/m | 40 Lm/ft
Blue: 27 Lm/m | 8 Lm/ft

EFFICACY Luminaire: 28 lm/W
Light source: 44 lm/W

LIFETIME L90B10 60.000h

HOUSING Aluminum, polyurethane

ELECTRICAL Power per meter/feet: 7.2 W/m
Voltage: 24 VDC

TEMPERATURE Tc max <75°C (167°F)
Operating: -25°C...+50°C (-13°F...122°F)

OTHER DETAILS IP67 protection
Dimmable
Install in well-ventilated areas only

DIMENSIONS Width: 16 mm (0.63")
Height: 16 mm (0.63")
Length: 1003 mm | 3.3'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.