



ULA S IP67 TUNABLE WHITE LIGHT

UlaS.IP67 AULSO IEC PWE ECL / TW56/Nx G4 09W 820/835 L1000


Luminaire segment




COLORS

White housing

PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



SPECTRUM	Warm LED: CRI 80+ 2000K
	Cold LED: CRI 80+ 3500K
	3-Step MacAdam
COVER	Clear
LUMINOUS FLUX*	Per segment: 791 lm
	Light source (per segment): 1242 lm
	Per meter/feet: 791 lm/m 241 lm/ft
EFFICACY	Luminaire: 82 lm/W
	Light source: 129 lm/W
LIFETIME	L90B10 60.000h
HOUSING	Aluminum, polyurethane
ELECTRICAL	Segment power: 9.6 W
	Power per meter/feet: 9.6 W/m
	Voltage: 24 VDC
TEMPERATURE	Tc max <75°C (167°F)
	Operating: -25°C...+50°C (-13°F...122°F)
OTHER DETAILS	IP67 protection
	Dimmable
	Install in well-ventilated areas only
DIMENSIONS	Width: 16 mm (0.63")
	Height: 16 mm (0.63")
	Length: 1003 mm 3.3'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.