





## NEMAN RECESSED

### Microprism

Product code: NM R LUM MP PW W17 827 0560 D

Article No.: F1RAMDAADXX0560D



<b>MOUNTING</b>	Recessed
<b>TYPE</b>	Individual luminaire
<b>CCT</b>	2700K
<b>CRI</b>	CRI 80+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>LUMENS LUMINAIRE</b>	1105 Lm
<b>LIGHT SOURCE</b>	1504 Lm
<b>EFFICACY LUMINAIRE</b>	106 Lm/W
<b>LIGHT SOURCE</b>	161 Lm/W
<b>LIFETIME</b>	L90B10 60.000h

<b>CONTROL</b>	DALI
----------------	------

<b>LUMINAIRE POWER</b>	10.4 W
<b>INPUT VOLTAGE</b>	220-240 VAC 50/60 Hz
	Integrated driver

<b>HOUSING</b>	Microprism light surface
<b>HOUSING COLOR</b>	Extruded aluminum, White color
<b>IP CLASS</b>	IP20 ingress protection
<b>OTHER DETAILS</b>	Lead cable 2m (6.5'), transparent

<b>DIMENSIONS</b>	Width: 48 mm / 1.89"
	Height: 41 mm / 1.61"
	Length: 577 mm / 1.9'

<b>MOUNTING HOLE</b>	568 x mm / 1.86' x 1.5"
----------------------	-------------------------



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
 All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.