



NEMAN RECESSED

Microprism

Product code: NM R LUM MP PW W17 827 1120 D

Article No.: F1RAMDAADXX1120D



| | |
|---------------------------|----------------------|
| MOUNTING | Recessed |
| TYPE | Individual luminaire |
| CCT | 2700K |
| CRI | CRI 80+ |
| COLOR CONSISTENCY | 3-Step MacAdam |
| LUMENS LUMINAIRE | 2209 Lm |
| LIGHT SOURCE | 3008 Lm |
| EFFICACY LUMINAIRE | 106 Lm/W |
| LIGHT SOURCE | 161 Lm/W |
| LIFETIME | L90B10 60.000h |

| | |
|----------------|------|
| CONTROL | DALI |
|----------------|------|

| | |
|------------------------|----------------------|
| LUMINAIRE POWER | 20.8 W |
| INPUT VOLTAGE | 220-240 VAC 50/60 Hz |
| | Integrated driver |

| | |
|----------------------|-----------------------------------|
| HOUSING | Microprism light surface |
| HOUSING COLOR | Extruded aluminum, White color |
| IP CLASS | IP20 ingress protection |
| OTHER DETAILS | Lead cable 2m (6.5'), transparent |

| | |
|-------------------|------------------------|
| DIMENSIONS | Width: 48 mm / 1.89" |
| | Height: 41 mm / 1.61" |
| | Length: 1137 mm / 3.7' |

| | |
|----------------------|-------------------------|
| MOUNTING HOLE | 1128 x mm / 3.7' x 1.5" |
|----------------------|-------------------------|



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
 All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.