



# ULA S RGB COLORFUL LIGHT

UlaS AULSI IEC AG CLR / RGB48/Nx G5 07W L1000


Luminaire segment




## COLORS

 Grey housing

## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



## SPECTRUM

3-Step MacAdam

## COVER

Clear

## LUMINOUS FLUX\*

Luminaire: 278 lm  
Light source : 316 lm

### Per meter/feet:

Red: 57 Lm/m | 17 Lm/ft  
Green: 183 Lm/m | 56 Lm/ft  
Blue: 38 Lm/m | 12 Lm/ft

## EFFICACY

Luminaire: 39 lm/W  
Light source: 44 lm/W

## LIFETIME

L90B10 60.000h

## HOUSING

Aluminum, plastic

## ELECTRICAL

Power per meter/feet: 7.2 W/m  
Voltage: 24 VDC

## OTHER DETAILS

IP40 ingress protection  
Dimmable

## DIMENSIONS

Width: 16 mm (0.63")  
Height: 11 mm (0.43")  
Lenght: 1003 mm | 3.3'

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.