

# ULA M IP67 RGB COLORFUL LIGHT

UlaM.IP67 AULMO IEC AG EOP / RGB-48/Nx G5 011W L1000


Luminaire segment




## COLORS

 Grey housing

## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



<b>SPECTRUM</b>	3-Step MacAdam
<b>COVER</b>	Opal
<b>LUMINOUS FLUX*</b>	<p>Luminaire: 216 lm Light source: 480 lm</p> <p><b>Per meter/feet:</b> Red: 47 Lm/m   14 Lm/ft Green: 138 Lm/m   42 Lm/ft Blue: 31 Lm/m   9 Lm/ft</p>
<b>EFFICACY</b>	<p>Luminaire: 19 lm/W Light source: 42 lm/W</p>
<b>LIFETIME</b>	L90B10 60.000h
<b>HOUSING</b>	Aluminum, polyurethane
<b>ELECTRICAL</b>	<p>Power per meter/feet: 11.52 W/m Voltage: 24 VDC</p>
<b>TEMPERATURE</b>	<p>Tc max &lt;75°C ( 167°F ) Operating: -25°C...+50°C ( -13°F...122°F )</p>
<b>OTHER DETAILS</b>	<p>IP67 protection Dimmable Install in well-ventilated areas only</p>
<b>DIMENSIONS</b>	<p>Width: 16 mm (0.63") Height: 26 mm (1.02") Length: 1003 mm   3.3'</p>

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.