

ULA M IP67 RGB COLORFUL LIGHT

UlaM.IP67 AULMO IEC PB EOP / RGB-48/Nx G5 07W L1000


Luminaire segment



COLORS

Black housing

PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



SPECTRUM	3-Step MacAdam
COVER	Opal
LUMINOUS FLUX*	Luminaire: 143 lm Light source: 316 lm Per meter/feet: Red: 29 Lm/m 9 Lm/ft Green: 94 Lm/m 29 Lm/ft Blue: 19 Lm/m 6 Lm/ft
EFFICACY	Luminaire: 20 lm/W Light source: 44 lm/W
LIFETIME	L90B10 60.000h
HOUSING	Aluminum, polyurethane
ELECTRICAL	Power per meter/feet: 7.2 W/m Voltage: 24 VDC
TEMPERATURE	Tc max <75°C (167°F) Operating: -25°C...+50°C (-13°F...122°F)
OTHER DETAILS	IP67 protection Dimmable Install in well-ventilated areas only
DIMENSIONS	Width: 16 mm (0.63") Height: 26 mm (1.02") Length: 1003 mm 3.3'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.