



ULA S IP67 WHITE LIGHT

Luminaire segment

ULA S IP67 LUM CL FL56-2/N4-822 AGY L1000

Article No.: C4AAPAMABXXL1000



| | |
|--------------------|-----------------|
| CCT | 2200K |
| CRI | CRI 80+ |
| COLOR CONSISTENCY | 3-Step MacAdam |
| COVER | Clear |
| LUMENS LUMINAIRE | 177 Lm |
| LIGHT SOURCE | 265 Lm |
| EFFICACY LUMINAIRE | 74 Lm/W |
| LIGHT SOURCE | 110 Lm/W |
| LIFETIME | L90B10 60.000 h |

| | |
|---------|------------------------|
| HOUSING | Aluminum, polyurethane |
|---------|------------------------|

| | |
|---------|--------------------|
| VOLTAGE | 24 VDC |
| WATTAGE | 2.4 W/m 0.7 W/ft |

| | |
|---------------|-----------------------------|
| MAX RUN | 24.5 m (80') |
| OTHER DETAILS | IP67 protection Dimmable |

| | |
|-----------------|---------------------------------|
| TEMPERATURE | Tc max <75°C (167°F) |
| OPERATING TEMP. | -25°C...+50°C (-13°F...122°F) |

| | |
|------------|---|
| DIMENSIONS | Width: 16 mm (0.63") Height: 16 mm (0.63") Length: 1000 mm (305") |
|------------|---|



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.