


FL-140-9/O2-850

White LED strips

Article No.: A1CBDAHXX



LIGHT TYPE	White
LEDs/M	140 LEDs/m
CCT	5000K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
PHOTOMETRIC	120° beam angle
LUMINOUS FLUX	1430 Lm/m (436 Lm/ft)
EFFICACY	149 Lm/W
LIFETIME	L70B50 50.000 h

CONTROL	Dimmable
---------	----------

VOLTAGE	24 VDC
WATTAGE	9.6 W/m 2.93 W/ft

CUTTING STEP	50 mm (1.97")
MAX RUN	10 m (33')
PACKING	10 m, 50 m or customized length per reel
DIMENSIONS	Width: 8 mm Height: 1.7 mm (0.07")

TEMPERATURE	Tc max <75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)
STORAGE TEMP.	-25°C...+80°C (-13°F...176°F)



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.