




## FL-168-9/N3-830

White LED strips

Article No.: A1HBBAEXX



LIGHT TYPE	White
LEDs/M	168 LEDs/m
CCT	3000K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
PHOTOMETRIC	120° beam angle
LUMINOUS FLUX	1470 Lm/m (448 Lm/ft)
EFFICACY	153 Lm/W
LIFETIME	L90B10 60.000 h

CONTROL	Dimmable
---------	----------

VOLTAGE	24 VDC
WATTAGE	9.6 W/m   2.93 W/ft

CUTTING STEP	41.65 mm (1.64")
MAX RUN	7 m (23')
PACKING	10 m, 50 m or customized length per reel
DIMENSIONS	Width: 8 mm Height: 1.2 mm (0.05")

TEMPERATURE	Tc max <75°C ( 167°F )
OPERATING TEMP.	-25°C...+50°C ( -13°F...122°F )
STORAGE TEMP.	-25°C...+80°C ( -13°F...176°F )



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.