




# FL175/NX G5 04W 035

White LED strips



<b>LIGHT TYPE</b>	White
<b>LEDs/M</b>	175 LEDs/m
<b>CCT</b>	3500K
<b>CRI</b>	CRI 95+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>PHOTOMETRIC</b>	120° beam angle
<b>LUMINOUS FLUX</b>	513 Lm/m (156 Lm/ft)
<b>EFFICACY</b>	107 Lm/W
<b>LIFETIME</b>	L90B10 60.000 h

<b>CONTROL</b>	Dimmable
----------------	----------

<b>VOLTAGE</b>	24 VDC
<b>WATTAGE</b>	4.8 W/m   1.46 W/ft

<b>CUTTING STEP</b>	40 mm (1.57")
<b>MAX RUN</b>	5 m (16')
<b>PACKING</b>	10 m, 50 m or customized length per reel
<b>DIMENSIONS</b>	Width: 5 mm Height: 1.62 mm (0.06")

<b>TEMPERATURE</b>	Tc max <75°C ( 167°F )
<b>OPERATING TEMP.</b>	-25°C...+50°C ( -13°F...122°F )
<b>STORAGE TEMP.</b>	-25°C...+80°C ( -13°F...176°F )



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.