

see drawings below for real representation

CE ROHS CARDE IN US SYEAR A+ ENERGY ELUROPE SYEAR A+ ENERGY CLASS

White housing Black louver

> 31 mm (1.22 in) 41 mm (1.61 in)

COLORS

PHOTOMETRICS

TECHNICAL DRAWING

34 mm (1.34 in) 48 mm (1.89 in)

90

## NEMAN X - RECESSED

## Neman-X R LUM PW X1 B D30 930 ND

Individual luminaire

Product code: NMX R LUM PW X1 B D30 930 N Article No.: F3RADABBBEN

MOUNTING	Recessed type	
SPECTRUM	3000K	
	CRI 90+	
	3-Step MacAdam	
OPTICS	30°	
LUMINOUS FLUX*	Luminaire: 141 Lm	
	Light source: 162 Lm	
EFFICACY	Luminaire: 88 Lm/W	
	Light source: 101 Lm/W	
LIFETIME	L90B10 60.000h	
DIMMING	not dimmable	
HOUSING	Aluminum, plastic	
ELECTRICAL	Luminaire power: 1.6 W	
	220-240 VAC 50/60 Hz	
	External driver included	
OTHER DETAILS	IP40 ingress protection	
DIMENSIONS	Width: 48mm / 1.9"	
	Height: 41mm / 1.61"	
	Length: 48 mm / 0.16'	

Ø

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.