

# NEMAN X - RECESSED

## Neman-X R LUM PW X1 B D30 935 DALI

Individual luminaire

Product code: NMX R LUM PW X1 B D30 935 D

Article No.: F3RADABBBFD


see drawings below for real representation




### COLORS



### PHOTOMETRICS



### TECHNICAL DRAWING



|                       |  |
|-----------------------|--|
| <b>MOUNTING</b>       | Recessed type  |
| <b>SPECTRUM</b>       | 3500K<br>CRI 90+<br>3-Step MacAdam   |
| <b>OPTICS</b>         | 30°  |
| <b>LUMINOUS FLUX*</b> | Luminaire: 146 Lm<br>Light source: 168 Lm                                  |
| <b>EFFICACY</b>       | Luminaire: 91 Lm/W<br>Light source: 105 Lm/W                               |
| <b>LIFETIME</b>       | L90B10 60.000h   |
| <b>DIMMING</b>        | DALI, PushDim  |
| <b>HOUSING</b>        | Aluminum, plastic  |
| <b>ELECTRICAL</b>     | Luminaire power: 1.6 W<br>220-240 VAC 50/60 Hz<br>External driver included |
| <b>OTHER DETAILS</b>  | IP40 ingress protection  |
| <b>DIMENSIONS</b>     | Width: 48mm / 1.9"<br>Height: 41mm / 1.61"<br>Length: 48 mm / 0.16'        |
| <b>MOUNTING HOLE</b>  | 39 x 38 mm / 0.13' x 0.12'   |

### LEDS LAYOUT



\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.