



# NEMAN PENDANT

Opal direct/indirect

Product code: NM P LUM OP PW W17W8 827 0560 D

Article No.: F2PAODKADXX0560D



<b>MOUNTING</b>	Pendant direct/indirect
<b>TYPE</b>	Individual luminaire
<b>CCT</b>	2700K
<b>CRI</b>	CRI 80+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>LUMENS LUMINAIRE</b>	1862 Lm
<b>LIGHT SOURCE</b>	2394 Lm
<b>DIR/IND PROPORTION</b>	62/38
<b>EFFICACY LUMINAIRE</b>	128 Lm/W
<b>LIGHT SOURCE</b>	184 Lm/W
<b>LIFETIME</b>	L90B10 60.000h

<b>CONTROL</b>	DALI
----------------	------

<b>LUMINAIRE POWER</b>	14.5 W
<b>INPUT VOLTAGE</b>	220-240 VAC 50/60 Hz Integrated driver

<b>HOUSING</b>	Opal light surface
<b>HOUSING COLOR</b>	Extruded aluminum, White color
<b>IP CLASS</b>	IP20 ingress protection
<b>OTHER DETAILS</b>	Suspension length 2m (6.5') Lead cable 2m (6.5'), transparent

<b>DIMENSIONS</b>	Width: 34 mm / 1.34" Height: 60 mm / 2.36" Length: 563 mm / 1.8'
-------------------	--



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.