



NEMAN PENDANT

Opal direct/indirect

Product code: NM P LUM OP PW W17W8 827 1120 D

Article No.: F2PAODKADXX1120D



| | |
|---------------------------|-------------------------|
| MOUNTING | Pendant direct/indirect |
| TYPE | Individual luminaire |
| CCT | 2700K |
| CRI | CRI 80+ |
| COLOR CONSISTENCY | 3-Step MacAdam |
| LUMENS LUMINAIRE | 3725 Lm |
| LIGHT SOURCE | 4788 Lm |
| DIR/IND PROPORTION | 62/38 |
| EFFICACY LUMINAIRE | 128 Lm/W |
| LIGHT SOURCE | 184 Lm/W |
| LIFETIME | L90B10 60.000h |

| | |
|----------------|------|
| CONTROL | DALI |
|----------------|------|

| | |
|------------------------|---|
| LUMINAIRE POWER | 29 W |
| INPUT VOLTAGE | 220-240 VAC 50/60 Hz Integrated driver |

| | |
|----------------------|--|
| HOUSING | Opal light surface |
| HOUSING COLOR | Extruded aluminum, White color |
| IP CLASS | IP20 ingress protection |
| OTHER DETAILS | Suspension length 2m (6.5') Lead cable 2m (6.5'), transparent |

| | |
|-------------------|---|
| DIMENSIONS | Width: 34 mm / 1.34" Height: 60 mm / 2.36" Length: 1123 mm / 3.7' |
|-------------------|---|



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.