



NEMAN PENDANT

Opal direct/indirect

Product code: NM P LUM OP PW W17W8 827 1400 N

Article No.: F2PAODKADXX1400N



| | |
|---------------------------|-------------------------|
| MOUNTING | Pendant direct/indirect |
| TYPE | Individual luminaire |
| CCT | 2700K |
| CRI | CRI 80+ |
| COLOR CONSISTENCY | 3-Step MacAdam |
| LUMENS LUMINAIRE | 4656 Lm |
| LIGHT SOURCE | 5985 Lm |
| DIR/IND PROPORTION | 62/38 |
| EFFICACY LUMINAIRE | 129 Lm/W |
| LIGHT SOURCE | 184 Lm/W |
| LIFETIME | L90B10 60.000h |

| | |
|----------------|--------|
| CONTROL | no dim |
|----------------|--------|

| | |
|------------------------|---|
| LUMINAIRE POWER | 36.2 W |
| INPUT VOLTAGE | 220-240 VAC 50/60 Hz Integrated driver |

| | |
|----------------------|--|
| HOUSING | Opal light surface |
| HOUSING COLOR | Extruded aluminum, White color |
| IP CLASS | IP20 ingress protection |
| OTHER DETAILS | Suspension length 2m (6.5') Lead cable 2m (6.5'), transparent |

| | |
|-------------------|---|
| DIMENSIONS | Width: 34 mm / 1.34" Height: 60 mm / 2.36" Length: 1403 mm / 4.6' |
|-------------------|---|



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.