





## MINIAX PENDANT

Product code: MiniaX P IND PWE.PWE BBK B280 D050 W23 840  
L1960 FO EU / PH



|                          |   |
|--------------------------|---|
| <b>MOUNTING</b>          | Pendant                                       |
| <b>TYPE</b>              | Individual                                    |
| <b>CCT</b>               | 4000K   |
| <b>CRI</b>               | CRI 80+                                       |
| <b>COLOR CONSISTENCY</b> | 3-Step MacAdam                                |
| <b>LUMINOUS FLUX</b>     | Luminaire: 3763 Lm<br>Light Source: 4628 Lm   |
| <b>EFFICACY</b>          | Luminaire: 131 Lm/W<br>Light Source: 182 Lm/W |
| <b>LIFETIME</b>          | L90B10 60.000h                                |

|                |        |
|----------------|--------|
| <b>CONTROL</b> | no dim |
|----------------|--------|

|                        |   |
|------------------------|---|
| <b>LUMINAIRE POWER</b> | 28.74 W                                   |
| <b>INPUT VOLTAGE</b>   | 220-240 VAC 50/60 Hz<br>Integrated driver |

|                        |  |
|------------------------|--|
| <b>LIGHT DIFFUSION</b> | 50°  |
| <b>HOUSING</b>         | Housing Color: White<br>Baffle Color: Baffle Black<br>Blackout Color: White 280 mm |
| <b>IP CLASS</b>        | IP20 ingress protection  |
| <b>OTHER DETAILS</b>   | Suspension length 2m (6.5')<br>Lead cable 2m (6.5'), transparent                   |

|                   |   |
|-------------------|---|
| <b>DIMENSIONS</b> | Width: 36 mm / 1.43"<br>Height: 58 mm / 2.29"<br>Length: 1967 mm / 6.5' |
|-------------------|---|



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.