





MINIAX PENDANT

Product code: MiniaX P STA PWE.XXX BBK B000 D050 W16 827
L1120 FO EU / PH



MOUNTING	Pendant
TYPE	Start module
CCT	2700K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 2380 Lm Light Source: 2928 Lm
EFFICACY	Luminaire: 113 Lm/W Light Source: 162 Lm/W
LIFETIME	L90B10 60.000h

CONTROL	no dim
----------------	--------

LUMINAIRE POWER	21.03 W
INPUT VOLTAGE	220-240 VAC 50/60 Hz Integrated driver

LIGHT DIFFUSION	50°
HOUSING	Housing Color: White Baffle Color: Baffle Black
IP CLASS	IP20 ingress protection
OTHER DETAILS	Suspension length 2m (6.5') Lead cable 2m (6.5'), transparent

DIMENSIONS	Width: 36 mm / 1.43" Height: 58 mm / 2.29" Length: 1124 mm / 3.7'
-------------------	---








Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.