



MINIAX RECESSED

Product code: MiniaX R IND PWE.PWE BBK B280 D050 W23 835
L1960 DA EU / PH



MOUNTING	Recessed
TYPE	Individual
CCT	3500K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 3753 Lm Light Source: 4616 Lm
EFFICACY	Luminaire: 130 Lm/W Light Source: 181 Lm/W
LIFETIME	L90B10 60.000h

CONTROL	DALI
----------------	------

LUMINAIRE POWER	28.8 W
INPUT VOLTAGE	220-240 VAC 50/60 Hz External driver included

LIGHT DIFFUSION	50°
HOUSING	Housing Color: White Baffle Color: Baffle Black Blackout Color: White 280 mm
IP CLASS	IP20 ingress protection

DIMENSIONS	Width: 49.6 mm / 1.95" Height: 39.1 mm / 1.53" Length: 1978 mm / 6.5'
-------------------	---








Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.