



## MINIAX RECESSED

Product code: MiniaX R STA PWE.XXX BBK B000 D050 W16 827  
L2240 FO EU / PH



<b>MOUNTING</b>	Recessed
<b>TYPE</b>	Start module
<b>CCT</b>	2700K
<b>CRI</b>	CRI 80+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>LUMINOUS FLUX</b>	Luminaire: 4761 Lm Light Source: 5856 Lm
<b>EFFICACY</b>	Luminaire: 118 Lm/W Light Source: 162 Lm/W
<b>LIFETIME</b>	L90B10 60.000h

<b>CONTROL</b>	no dim
----------------	--------

<b>LUMINAIRE POWER</b>	40.25 W
<b>INPUT VOLTAGE</b>	220-240 VAC 50/60 Hz External driver included

<b>LIGHT DIFFUSION</b>	50°
<b>HOUSING</b>	Housing Color: White Baffle Color: Baffle Black
<b>IP CLASS</b>	IP20 ingress protection

<b>DIMENSIONS</b>	Width: 49.6 mm / 1.95" Height: 39.1 mm / 1.53" Length: 2249 mm / 7.4'
-------------------	---








Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.