





NEMAN WALL OPAL

Product code: NM W LUM OP PW W17 827 1120 D
 Article No.: F1WAODAADX1120D



| | |
|---------------------------|----------------------|
| MOUNTING | Wall |
| TYPE | Individual luminaire |
| CCT | 2700K |
| CRI | CRI 80+ |
| COLOR CONSISTENCY | 3-Step MacAdam |
| LUMENS LUMINAIRE | 2195 Lm |
| LIGHT SOURCE | 3008 Lm |
| EFFICACY LUMINAIRE | 106 Lm/W |
| LIGHT SOURCE | 161 Lm/W |
| LIFETIME | L90B10 60.000h |

| | |
|----------------|------|
| CONTROL | DALI |
|----------------|------|

| | |
|------------------------|---|
| LUMINAIRE POWER | 20.8 W |
| INPUT VOLTAGE | 220-240 VAC 50/60 Hz Integrated driver |

| | |
|----------------------|--------------------------------|
| HOUSING | Opal light surface |
| HOUSING COLOR | Extruded aluminum, White color |
| IP CLASS | IP40 ingress protection |

| | |
|------------------------|-------------------------------|
| OPERATING TEMP. | -25°C...+50°C (-13°F...122°F) |
| STORAGE TEMP. | -25°C...+80°C (-13°F...176°F) |

| | |
|-------------------|---|
| DIMENSIONS | Width: 34 mm / 1.34" Height: 60 mm / 2.36" Length: 1123 mm / 3.7' |
|-------------------|---|



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
 All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.