


see drawings below for real representation




COLORS

- White housing
- Black louver

PHOTOMETRICS



TECHNICAL DRAWING



NEMAN X - RECESSED

Neman-X R LUM PW X1 B D30 935 DALI
Individual luminaire

Product code: NMX R LUM PW X1 B D30 935 D
Article No.: F3RADABBBFD

MOUNTING	Recessed type
SPECTRUM	3500K CRI 90+ 3-Step MacAdam
OPTICS	30°
LUMINOUS FLUX*	Luminaire: 146 Lm Light source: 168 Lm
EFFICACY	Luminaire: 91 Lm/W Light source: 105 Lm/W
LIFETIME	L90B10 60.000h
DIMMING	DALI, PushDim
HOUSING	Aluminum, plastic
ELECTRICAL	Luminaire power: 1.6 W 220-240 VAC 50/60 Hz External driver included
OTHER DETAILS	IP40 ingress protection
DIMENSIONS	Width: 48mm / 1.9" Height: 41mm / 1.61" Length: 48 mm / 0.16'
MOUNTING HOLE	39 x 38 mm / 0.13' x 0.12'
LEDS LAYOUT	



* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.