



# NERIS PENDANT OPAL


Neris P LUM OP PWE W17C 827 L1120 ND

Individual luminaire




 White body + Opal


## PHOTOMETRICS



## Individual luminaire layout



## TECHNICAL DRAWING



<b>MOUNTING</b>	Pendant type
<b>SPECTRUM</b>	2700K CRI 80+ 3-Step MacAdam
<b>LUMINOUS FLUX*</b>	Luminaire: 1963 Lm Light source: 2968 Lm
<b>EFFICACY</b>	Luminaire: 94 Lm/W Light source: 158 Lm/W
<b>LIFETIME</b>	L90B10 60.000h
<b>DIMMING</b>	not dimmable
<b>HOUSING</b>	Opal light surface Extruded aluminum, White color
<b>ELECTRICAL</b>	Luminaire power: 20.9 W 220-240 VAC 50/60 Hz Integrated driver
<b>OTHER DETAILS</b>	IP20 ingress protection. Lead cable 2m (6.5'), transparent
<b>DIMENSIONS</b>	Width: 60 mm / 2.36" Height: 80 mm / 3.15" Length: 1123 mm / 3.7'

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ . All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.