

# NERIS SURFACE MICROPRISM




## NERIS S LUM MP PW W17C 827 L1400 ND

Individual luminaire


Product code: NR S LUM MP PW W17 827 1400 N

Article No.: F8SAMDAADXX1400N




 White body + Microprism


### PHOTOMETRICS



### Individual luminaire layout



### TECHNICAL DRAWING



<b>MOUNTING</b>	Surface type
<b>SPECTRUM</b>	2700K CRI 80+ 3-Step MacAdam
<b>LUMINOUS FLUX*</b>	Luminaire: 2614 Lm Light source: 3710 Lm
<b>EFFICACY</b>	Luminaire: 100 Lm/W Light source: 158 Lm/W
<b>LIFETIME</b>	L90B10 60.000h
<b>DIMMING</b>	not dimmable
<b>HOUSING</b>	Microprism light surface Extruded aluminum, White color
<b>ELECTRICAL</b>	Luminaire power: 26.1 W 220-240 VAC 50/60 Hz Integrated driver
<b>OTHER DETAILS</b>	IP20 ingress protection. Lead cable 2m (6.5'), transparent
<b>DIMENSIONS</b>	Width: 60 mm / 2.36" Height: 80 mm / 3.15" Length: 1403 mm / 4.6'

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ . All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.