





## QUADRO SURFACE

Quadro S 8W 50D.DIF Nx T930 PWE BBK.MAT XX / PH




---

<b>MOUNTING TYPE</b>	Surface
<b>CCT</b>	3000K
<b>CRI</b>	CRI T90+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>OPTIC</b>	50° Diffused
<b>LUMINOUS FLUX</b>	Luminaire: 902 Lm Light Source: 1292 Lm
<b>EFFICACY</b>	Luminaire: 109 Lm/W Light Source: 156 Lm/W
<b>LIFETIME</b>	L90B10 60.000h

---

<b>CONTROL</b>	Driver not included
----------------	---------------------

---

<b>LUMINAIRE POWER</b>	8.28 W
<b>INPUT VOLTAGE</b>	max 30V DC
<b>INPUT CURRENT</b>	300 mA

---

<b>HOUSING COLOR</b>	Extruded aluminum, White
<b>BAFFLE COLOR</b>	Black Matt

---

<b>DIMENSIONS</b>	Width: 64 mm / 2.25" Length: 68 mm / 2.66" Height: 25 mm / 0.98"
-------------------	--

---



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.