



NEMAN PENDANT

Opal direct/indirect

Product code: NM P LUM OP PW W17W8 827 0840 N

Article No.: F2PAODKADXX0840N



MOUNTING	Pendant direct/indirect
TYPE	Individual luminaire
CCT	2700K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
LUMENS LUMINAIRE	2794 Lm
LIGHT SOURCE	3591 Lm
DIR/IND PROPORTION	62/38
EFFICACY LUMINAIRE	129 Lm/W
LIGHT SOURCE	184 Lm/W
LIFETIME	L90B10 60.000h

CONTROL	no dim
----------------	--------

LUMINAIRE POWER	21.7 W
INPUT VOLTAGE	220-240 VAC 50/60 Hz Integrated driver

HOUSING	Opal light surface
HOUSING COLOR	Extruded aluminum, White color
IP CLASS	IP20 ingress protection
OTHER DETAILS	Suspension length 2m (6.5') Lead cable 2m (6.5'), transparent

DIMENSIONS	Width: 34 mm / 1.34" Height: 60 mm / 2.36" Length: 843 mm / 2.8'
-------------------	--



Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.