



# ULA S TUNABLE WHITE LIGHT

UlaS AULSI IEC AG CLR / TW56/Nx G4 09W 820/835 L1000


Luminaire segment




## COLORS



## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



<b>SPECTRUM</b>	Warm LED: CRI 80+ 2000K
	Cold LED: CRI 80+ 3500K
	3-Step MacAdam
<b>COVER</b>	Clear
<b>LUMINOUS FLUX*</b>	Per segment: 1084 lm
	Light source (per segment): 1232 lm
	Per meter/feet: 1084 lm/m   330 lm/ft
<b>EFFICACY</b>	Luminaire: 113 lm/W
	Light source: 128 lm/W
<b>LIFETIME</b>	L90B10 60.000h
<b>HOUSING</b>	Aluminum, plastic
<b>ELECTRICAL</b>	Segment power: 9.6 W
	Power per meter/feet: 9.6 W/m
	Voltage: 24 VDC
<b>OTHER DETAILS</b>	IP40 ingress protection
	Dimmable
<b>DIMENSIONS</b>	Width: 16 mm (0.63")
	Height: 11 mm (0.43")
	Length: 1003 mm   3.3'

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.