



# ULA S TUNABLE WHITE LIGHT

UlaS AULSI IEC AG CLR / TW56/Nx G4 09W 820/840 L1000


Luminaire segment




## COLORS



## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



|                       |                                       |
|-----------------------|---------------------------------------|
| <b>SPECTRUM</b>       | Warm LED: CRI 80+ 2000K               |
|                       | Cold LED: CRI 80+ 4000K               |
|                       | 3-Step MacAdam                        |
| <b>COVER</b>          | Clear                                 |
| <b>LUMINOUS FLUX*</b> | Per segment: 1086 lm                  |
|                       | Light source (per segment): 1234 lm   |
|                       | Per meter/feet: 1086 lm/m   331 lm/ft |
| <b>EFFICACY</b>       | Luminaire: 113 lm/W                   |
|                       | Light source: 129 lm/W                |
| <b>LIFETIME</b>       | L90B10 60.000h                        |
| <b>HOUSING</b>        | Aluminum, plastic                     |
| <b>ELECTRICAL</b>     | Segment power: 9.6 W                  |
|                       | Power per meter/feet: 9.6 W/m         |
|                       | Voltage: 24 VDC                       |
| <b>OTHER DETAILS</b>  | IP40 ingress protection               |
|                       | Dimmable                              |
| <b>DIMENSIONS</b>     | Width: 16 mm (0.63")                  |
|                       | Height: 11 mm (0.43")                 |
|                       | Length: 1003 mm   3.3'                |

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.