



# ULA S WHITE LIGHT

UlaS AULSI IEC AG CLR / FL112/Nx G4 04W 820 1000

Luminaire segment




## COLORS




Grey housing

## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



## SPECTRUM

2000K  
CRI 80+  
3-Step MacAdam

## COVER

Clear

## LUMINOUS FLUX\*

Per segment: 431 lm  
Light source (per segment): 490 lm  
Per meter/feet: 431 lm/m | 131 lm/ft

## EFFICACY

Luminaire: 90 lm/W  
Light source: 102 lm/W

## LIFETIME

L90B10 60.000h

## HOUSING

Aluminum, plastic

## ELECTRICAL

Segment power: 4.8 W  
Power per meter/feet: 4.8 W/m  
Voltage: 24 VDC

## OTHER DETAILS

IP40 ingress protection  
Dimmable

## DIMENSIONS

Width: 16 mm (0.63")  
Height: 11 mm (0.43")  
Length: 1003 mm | 3.3'

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.