



ULA S WHITE LIGHT

UlaS AULSI IEC PB CLR / FL112/Nx G4 04W 820 1000


Luminaire segment




COLORS

 Black housing

PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



| | |
|-----------------------|---|
| SPECTRUM | 2000K CRI 80+ 3-Step MacAdam |
| COVER | Clear |
| LUMINOUS FLUX* | Per segment: 431 lm Light source (per segment): 490 lm Per meter/feet: 431 lm/m 131 lm/ft |
| EFFICACY | Luminaire: 90 lm/W Light source: 102 lm/W |
| LIFETIME | L90B10 60.000h |
| HOUSING | Aluminum, plastic |
| ELECTRICAL | Segment power: 4.8 W Power per meter/feet: 4.8 W/m Voltage: 24 VDC |
| OTHER DETAILS | IP40 ingress protection Dimmable |
| DIMENSIONS | Width: 16 mm (0.63") Height: 11 mm (0.43") Length: 1003 mm 3.3' |

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.