



ULA S WHITE LIGHT


UlaS AULSI IEC PB CLR / FL112/Nx G4 04W 822 1000
Luminaire segment




COLORS

Black housing

PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



SPECTRUM	2200K CRI 80+ 3-Step MacAdam
COVER	Clear
LUMINOUS FLUX*	Per segment: 467 lm Light source (per segment): 531 lm Per meter/feet: 467 lm/m 142 lm/ft
EFFICACY	Luminaire: 97 lm/W Light source: 111 lm/W
LIFETIME	L90B10 60.000h
HOUSING	Aluminum, plastic
ELECTRICAL	Segment power: 4.8 W Power per meter/feet: 4.8 W/m Voltage: 24 VDC
OTHER DETAILS	IP40 ingress protection Dimmable
DIMENSIONS	Width: 16 mm (0.63") Height: 11 mm (0.43") Lenght: 1003 mm 3.3'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.