

ULA M RGB COLORFUL LIGHT

UlaM AULMI IBC AG OPL / RGB-48/Nx G5 07W L1000


Luminaire segment




COLORS

 Grey housing

PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



SPECTRUM	3-Step MacAdam
COVER	Opal
LUMINOUS FLUX*	Luminaire: 152 lm Light source: 316 lm Per meter/feet: Red: 31 Lm/m 10 Lm/ft Green: 100 Lm/m 30 Lm/ft Blue: 21 Lm/m 6 Lm/ft
EFFICACY	Luminaire: 21 lm/W Light source: 44 lm/W
LIFETIME	L90B10 60.000h
HOUSING	Aluminum, plastic
ELECTRICAL	Power per meter/feet: 7.2 W/m Voltage: 24 VDC
OTHER DETAILS	IP40 ingress protection Dimmable
DIMENSIONS	Width: 16 mm (0.63") Height: 21 mm (0.82") Length: 1003 mm 3.3'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.
Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.