


# ULA M RGB COLORFUL LIGHT

UlaM AULMI IBC PW OPL / RGB-48/Nx G5 07W L1000


Luminaire segment




## COLORS

 White housing

## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



## SPECTRUM

3-Step MacAdam

## COVER

Opal

## LUMINOUS FLUX\*

Luminaire: 152 lm  
Light source: 316 lm

### Per meter/feet:

Red: 31 Lm/m | 10 Lm/ft  
Green: 100 Lm/m | 30 Lm/ft  
Blue: 21 Lm/m | 6 Lm/ft

## EFFICACY

Luminaire: 21 lm/W  
Light source: 44 lm/W

## LIFETIME

L90B10 60.000h

## HOUSING

Aluminum, plastic

## ELECTRICAL

Power per meter/feet: 7.2 W/m  
Voltage: 24 VDC

## OTHER DETAILS

IP40 ingress protection  
Dimmable

## DIMENSIONS

Width: 16 mm (0.63")  
Height: 21 mm (0.82")  
Length: 1003 mm | 3.3'

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.  
Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.