





# ULA M

UlaS AULSI IEC AGY CLR / RGB48/Nx G5 011W L1000



<b>TYPE</b>	RGB
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>LUMINOUS FLUX</b>	Luminaire: 230 Lm Light Source: 480 Lm Red: 50 Lm Green: 147 Lm Blue: 33 Lm
<b>EFFICACY</b>	Luminaire: 20 Lm/W Light Source: 42 Lm/W
<b>LIFETIME</b>	L90B10 60.000h

<b>CONTROL</b>	Dimmable
----------------	----------

<b>LUMINAIRE POWER</b>	11.52 W
<b>INPUT VOLTAGE</b>	24V DC

<b>COVER</b>	Opal
<b>HOUSING</b>	Extruded aluminum, Grey
<b>IP CLASS</b>	IP40 ingress protection
<b>OTHER DETAILS</b>	Luminaire segment

<b>DIMENSIONS</b>	Width: 16 mm / 0.63" Height: 21 mm / 0.82" Length: 1003 mm / 3.3'
-------------------	-------------------------------------------------------------------------



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.