




# ULA M WHITE LIGHT

UlaM AULMI IEC PW EOP / FL112/Nx G4 04W 820 1000


Luminaire segment




## COLORS

 White housing

## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



16 mm  
(0.63 in)

**SPECTRUM** 2000K  
CRI 80+  
3-Step MacAdam

**COVER** Opal

**LUMINOUS FLUX\*** Per segment: 235 lm  
Light source (per segment): 490 lm  
Per meter/feet: 235 lm/m | 72 lm/ft

**EFFICACY** Luminaire: 49 lm/W  
Light source: 102 lm/W

**LIFETIME** L90B10 60.000h

**HOUSING** Aluminum, plastic

**ELECTRICAL** Segment power: 4.8 W  
Power per meter/feet: 4.8 W/m  
Voltage: 24 VDC

**OTHER DETAILS** IP40 ingress protection  
Dimmable

**DIMENSIONS** Width: 16 mm (0.63")  
Height: 21 mm (0.82")  
Length: 1003 mm | 3.3'

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.