



ULA M WHITE LIGHT

ULA M LUM FL-112-4/N3-820 AG L375

Luminaire segment

Product code: ULAM LUM OP FL112-4N3-820 AG 0375


Article No.: C2ABBBAAAXXB0375




COLORS



PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



SPECTRUM

2000K
CRI 80+
3-Step MacAdam

COVER

Opal

LUMINOUS FLUX*

Per segment: 91 lm
Light source (per segment): 190 lm
Per meter/feet: 243 lm/m | 74 lm/ft

EFFICACY

Luminaire: 51 lm/W
Light source: 106 lm/W

LIFETIME

L90B10 60.000h

HOUSING

Aluminum, plastic

ELECTRICAL

Segment power: 1.8 W
Power per meter/feet: 4.8 W/m
Voltage: 24 VDC

OTHER DETAILS

IP40 ingress protection
Dimmable

DIMENSIONS

Width: 16 mm (0.63")
Height: 21 mm (0.82")
Length: 378 mm | 1.2'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.