



# ULA M WHITE LIGHT

ULA M LUM FL-112-4/N3-820 AG L875

Luminaire segment

Product code: ULAM LUM OP FL112-4N3-820 AG 0875

Article No.: C2ABBBAAAXXB0875




## COLORS




Grey housing

## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



## SPECTRUM

2000K  
CRI 80+  
3-Step MacAdam

## COVER

Opal

## LUMINOUS FLUX\*

Per segment: 213 lm  
Light source (per segment): 443 lm  
Per meter/feet: 243 lm/m | 74 lm/ft

## EFFICACY

Luminaire: 51 lm/W  
Light source: 105 lm/W

## LIFETIME

L90B10 60.000h

## HOUSING

Aluminum, plastic

## ELECTRICAL

Segment power: 4.2 W  
Power per meter/feet: 4.8 W/m  
Voltage: 24 VDC

## OTHER DETAILS

IP40 ingress protection  
Dimmable

## DIMENSIONS

Width: 16 mm (0.63")  
Height: 21 mm (0.82")  
Length: 878 mm | 2.9'

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ . All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.