



ULA S TUNABLE WHITE LIGHT

ULA S LUM TW-56-9/N3-820/835 AG L375

Luminaire segment

Product code: ULAS LUM CL TW56-9N3-820835 AG 0375


Article No.: C1AAFABAAAFB0375




COLORS

 Grey housing

PHOTOMETRICS




SEGMENT LAYOUT



Luminaire type segment

TECHNICAL DRAWING



SPECTRUM

Warm LED: CRI 80+ 2000K

Cold LED: CRI 80+ 3500K

3-Step MacAdam

COVER

Clear

LUMINOUS FLUX*

Per segment: 369 lm

Light source (per segment): 420 lm

Per meter/feet: 1119 lm/m | 341 lm/ft

EFFICACY

Luminaire: 103 lm/W

Light source: 117 lm/W

LIFETIME

L90B10 60.000h

HOUSING

Aluminum, plastic

ELECTRICAL

Segment power: 3.6 W

Power per meter/feet: 9.6 W/m

Voltage: 24 VDC

OTHER DETAILS

IP40 ingress protection

Dimmable

DIMENSIONS

Width: 16 mm (0.63")

Height: 11 mm (0.43")

Length: 378 mm | 1.2'

* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are $\pm 15\%$. Allowed measurement uncertainty $\pm 7\%$.

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.