



# ULA S TUNABLE WHITE LIGHT

**ULA S LUM TW-56-9/N3-820/835 AG L625**

Luminaire segment

Product code: ULAS LUM CL TW56-9N3-820835 AG 0625


Article No.: C1AAFABAAAFB0625




## COLORS

 Grey housing

## PHOTOMETRICS




## SEGMENT LAYOUT



Luminaire type segment

## TECHNICAL DRAWING



## SPECTRUM

Warm LED: CRI 80+ 2000K

Cold LED: CRI 80+ 3500K

3-Step MacAdam

## COVER

Clear

## LUMINOUS FLUX\*

Per segment: 615 lm

Light source (per segment): 699 lm

Per meter/feet: 1119 lm/m | 341 lm/ft

## EFFICACY

Luminaire: 103 lm/W

Light source: 117 lm/W

## LIFETIME

L90B10 60.000h

## HOUSING

Aluminum, plastic

## ELECTRICAL

Segment power: 6 W

Power per meter/feet: 9.6 W/m

Voltage: 24 VDC

## OTHER DETAILS

IP40 ingress protection

Dimmable

## DIMENSIONS

Width: 16 mm (0.63")

Height: 11 mm (0.43")

Length: 628 mm | 2.1'

\* Luminous flux values are based on tests with white housing. Lower luminous flux values might apply for other housing colors.

Possible allowed deviation of optical and electrical values are  $\pm 15\%$ . Allowed measurement uncertainty  $\pm 7\%$ .

All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.