





AQUA

RGBW-48-9/N4-825

RGB+W

Article No.: B14EBKACXX



CCT	2500K
CRI	CRI 80+
COLOR CONSISTENCY	3-Step MacAdam
LIGHT TYPE	RGBW
LEDs/M	48 LEDs/m
LUMINOUS FLUX	Total: 454 Lm/m (138 Lm/ft) White LED only: 249 Lm/m (76 Lm/ft) RGB LED only: 316 Lm/m (96 Lm/ft)
EFFICACY	47 Lm/W
LIFETIME	L90B10 60.000 h

CONTROL	Dimmable
---------	----------

VOLTAGE	24 VDC
WATTAGE	9.6 W/m 2.9 W/ft

CUTTING STEP	125 mm (4.92")
MAX RUN	8 m (26')
OTHER DETAILS	IP67 protection

TEMPERATURE	Tc max <75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)

DIMENSIONS	Width: 12 mm (0.47") Height: 4 mm (0.16")
------------	--

MOUNTING PROFILE	Polycarbonate UV and Salt water resistant
------------------	--



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.