



ATLANTIS SIDE

FL112-1/D4-850

White

Article No.: B2S1BNJAHXX



| | |
|-------------------|---------------------|
| CCT | 5000K |
| CRI | CRI 80+ |
| COLOR CONSISTENCY | 3-Step MacAdam |
| LUMINOUS FLUX | 154 Lm/m (47 Lm/ft) |
| EFFICACY | 80 Lm/W |
| LIFETIME | L70B50 50.000 h |

| | |
|---------|----------|
| CONTROL | Dimmable |
|---------|----------|

| | |
|---------|----------------------|
| VOLTAGE | 24 VDC |
| WATTAGE | 1.92 W/m 0.59 W/ft |

| | |
|---------------|--|
| CUTTING STEP | 62.5 mm (2.46") |
| MAX RUN | 5 m (16') |
| OTHER DETAILS | IP67 protection Bend radius: 15 cm (5.9") |

| | |
|-----------------|-------------------------------|
| TEMPERATURE | Tc max <75°C (167°F) |
| OPERATING TEMP. | -25°C...+50°C (-13°F...122°F) |

| | |
|------------|---|
| DIMENSIONS | Width: 15 mm (0.59") Height: 19 mm (0.75") |
|------------|---|



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.