



ATLANTIS G2 TOP

AtlantisG2Top IB RWE.EOP / TW2 112/Nx G5 09W 827 L1000



CCT	Warm: 2700K Cold: 5700K
CRI	Warm: 80+ Cold: 80+
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	804 Lm/m (245 Lm/ft)
EFFICACY	84 Lm/W
LIFETIME	L90B10 60.000 h

CONTROL	Dimmable
----------------	----------

VOLTAGE	24 VDC
WATTAGE	9.6 W/m 2.93 W/ft

CUTTING STEP	62.5 mm
OTHER DETAILS	IP67 protection Bend radius: 15 cm (5.9")

TEMPERATURE	Tc max <75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)

DIMENSIONS	Width: 14 mm ±1mm (0.55" ±0.04") Height: 16 mm ±2mm (0.63" ±0.07") Length: up to 4.5m ±3mm/meter (15"±0.11"/m)
-------------------	---



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.